



World Class Clampseal® Blowdown Valves

- *One-piece Gland*
- *In-line Servicing*
- *Easy-to-use Spinner Handle*



Conval Clampseal® Blowdown Service Valves provide necessary control for continuous boiler or turbine blowdown and bottom blow-off service.



DESIGN FEATURES

In-line Serviceability

Conval continuous and tandem blowdown valves are fully serviceable in-line using standard Conval tools.

Uniform Single-piece Gland

Proven, corrosion-inhibited, high-density graphite packing is loaded uniformly with a one-piece gland. This eliminates the potential for stem damage or packing leaks from gland cocking.

Cartridge-type Packing Chamber

With pressure-assisted bonnet seal, the chamber allows rapid access to valve trim for inspection and maintenance. Pressure boundary is sealed at the smallest diameter possible, to ensure maximum strength and low stress.

Pressure Seal Backseat

The pressure seal backseat provides maximum valve integrity by ensuring a positive internal stop for the valve stem and disc assembly. It also securely isolates packing from line pressure when valve is fully open, to increase packing life.

STANDARD SIZES

Continuous: 3/4" through 3" SW and BW
Venturi tube orifice size 1/8" thru 5/8"
Tandem: 1" thru 3" SW, BW or Flanged

PRESSURE RATING

Continuous: ASME/ANSI Class 900 through 4500
Tandem: ASME/ANSI Class 900 through 4500

STANDARD MATERIALS

Continuous: Low Alloy SA 182-F22 and F91
Tandem: Carbon Steel A105, Low Alloy F22 or F91
Other materials available upon request.

How to Order

For continuous blowdown service, use "N" in the Valve Design modifier and "J" in the Special Feature modifier of the figure number (for example, 1" 13N2J-F22). Indicate orifice size or inlet pressure and required maximum flow.

For tandem blowdown service, use "B" in the Valve Design modifier and "HJ" in the Special Feature modifier of the figure number (for example, 1" 12B2HJ-F22). Indicate right or left hand assembly.

ISO 9001 certified since 1992

Conval INC.

World Headquarters: 96 Phoenix Avenue, Enfield, CT 06082 USA

Phone (860) 749-0761 Fax (860) 763-3557

e-mail: sales@Conval.com www.Conval.com



Conval's policy is one of continuous development and improvement. Every effort is made to produce up-to-date literature but this catalog should not be regarded as an infallible guide to current specifications and does not form part of any contract. Conval reserves the right to make product improvements and changes without prior notice.